




Email: sales@bighandsbuildingsupplies.com.au

Shop Address: 60-68 Hampstead Road, Auburn 2144



PIR panel made by a PIR (Polyisocyanurate) fire-retardant core and high performing thermal properties. It's FM Approved to FM 4880 &4881, which recommended to improve fire performance for insurance purposes.

The polyisocyanurate foam core provides high thermal resistance, helping to maintain comfortable indoor temperatures and reduce energy consumption for heating or cooling.

Despite their superior insulation properties, PIR wall panels are lightweight, making them easy to handle, transport, and install.


Additionally, they offer durability and structural stability, contributing to the longevity of the building envelope.



PIR Sandwich Panel

Exterior Wall & Facade





Core ► PIR (Polyisocyanurate); 40kg/m³

External Material ► PPGI/PPGL: 0.4mm~0.7mm

External Finishes > Smooth,Lined,Microwave

External Colour Options White grey. Other colours available subject to minimum order quantities.

Internal Material ▶ PPGI/PPGL: 0.4mm~0.7mm

Internal Finishes

Smooth, Lined, Microwave

Internal Colour Options

White grey. Other colours available subject to minimum order quantities.

Thermal Conductivity (W/m ⋅ K) ► 0.02

Overlap

Hidden Screw

Core ► PIR (Polyisocyanurate); 40kg/m³

Width (cover mm) ▶ 1120

Thickness (mm) ▶

30/35/50

Length (mm) ▶

2.1/2.4/3.0 or Customized (Order Start 1000sqm)

External Material >

PPGI/PPGL: 0.6mm

SUS304: 0.5mm

External Finishes >

Smooth,Lined,Microwave

External Colour Options >

White grey. Other colours available subject to minimum order quantities.

Internal Material >

PPGI/PPGL: 0.6mm

SUS304: 0.5mm

Internal Finishes

Smooth,Lined,Microwave

Internal Colour Options >

White grey. Other colours available subject to minimum order quantities.

Thermal Conductivity (W/m ⋅ K) > 0.02

Overlap ► C Plug In



Core ► PIR (Polyisocyanurate); 40kg/m³

Lined

Microwave

Internal wall & ceiling

Width (cover mm) ▶ 1000

Thickness (mm) ▶

40/50/75/80/100/120/150

Length (mm) ▶

2.1/2.4/3.0 or Customized (Order Start 1000sqm)

External Material >

PPGI/PPGL: 0.4mm~0.7mm

External Finishes >

Corrugated

External Colour Options >

White grey.

Other colours available subject to minimum order quantities.

Internal Material

PPGI/PPGL: 0.4mm~0.7mm

Internal Finishes >

Smooth,Lined,Microwave

Internal Colour Options >


White grey.

Other colours available subject to minimum order quantities.

Thermal Conductivity (W/m ⋅ K) ► 0.02

Overlap ► Hidden Screw





Cold storage internal wall & ceiling

Core ► PIR (Polyisocyanurate); 40kg/m³

Width (cover mm) ▶ 1000/1120

Thickness (mm) ▶

75mm/150mm

Length (mm) ▶

2.1/2.4/3.0 or Customized (Order Start 1000sqm)

External Material >

PPGI/PPGL: 0.6mm SUS304: 0.5mm

External Finishes >

Smooth,Lined,Microwave

External Colour Options >

White grey. Other colours available subject to minimum order quantities.

Internal Material

PPGI/PPGL: 0.6mm SUS304: 0.5mm

Internal Finishes


Smooth,Lined,Microwave


Internal Colour Options >

White grey. Other colours available subject to minimum order quantities.

Thermal Conductivity (W/m ⋅ K) ► 0.02

Overlap M Plug In





Visible Neil Roof

Core ► PIR (Polyisocyanurate); 40kg/m³

Lined

Width (cover mm) ▶ 1000

Thickness (mm) ▶

20/30/40/50/60/75/80/100/125

Length (mm)

2.1/2.4/3.0 or Customized (Order Start 1000sqm)

External Material >

PPGI/PPGL: 0.4mm~0.7mm

External Finishes >

Trapezoidal Profile

External Colour Options >

White grey. Other colours available subject to minimum order quantities.

Internal Material

PPGI/PPGL: 0.4mm~0.7mm Aluminum Foil / White paper film

Internal Finishes

Smooth,Lined,Microwave Aluminum Foil / White paper film

Internal Colour Options >

White grey. Other colours available subject to minimum order quantities.

Thermal Conductivity (W/m ⋅ K) > 0.02

Overlap ► screw

